

Date Printed 27.02.2019

Version number 1

Revision Date 21.02.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier Silver Paint Diluent (100ml)

· Trade name: 4-methylpentan-2-one

· Article number: AGR1272

• CAS Number: 108-10-1 • EC number: 203-550-1 • Index number: 606-004-00-4

• 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.

- · Application of the substance / the preparation: Organic solvent diluent, used in microscopy.
- · 1.3 Details of the supplier of the safety data sheet
- · Supplier.

Agar Scientific Ltd
Parsonage Lane
Stansted CM24 8GF
United Kingdom
sales@agarscientific.com
Tel: +44 (0) 1279 813 519

- · Further information obtainable from: Technical Support
- **1.4 Emergency telephone number:** 24 hours: +44 (0)1856 407333

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.

Eye Irrit. 2 H319 Causes serious eye irritation. STOT SE 3 H335 May cause respiratory irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The substance is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02 GHS07

- · Signal word Danger
- · Hazard statements

H225 Highly flammable liquid and vapour.

H332 Harmful if inhaled.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

(Contd. on page 2)



Date Printed 27.02.2019 Version number 1 Revision Date 21.02.2019

Trade name: 4-methylpentan-2-one

(Contd. of page 1)

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.1 Chemical characterisation: Substances

· CAS No. Description

108-10-1 4-methylpentan-2-one

· Identification number(s)

· EC number: 203-550-1

· Index number: 606-004-00-4

SECTION 4: First aid measures

· 4.1 Description of first aid measures First aider: Pay attention to self-protection!

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

IF exposed or if you feel unwell: Call a POISON CENTRE or doctor/physician. If unconscious place in recovery position and seek medical advice. Never give anything by mouth to an unconscious person or a person with cramps. Change contaminated, saturated clothing. Do not leave affected person unattended.

After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

No adverse effects are anticipated from inhalation.

Call a POISON CENTRE/doctor/.... Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

After skin contact:

After contact with skin, wash immediately with plenty of water and soap. Remove contaminated, saturated clothing immediately. In case of skin reactions, consult a physician.

· After eye contact:

Rinse opened eye under running water. If symptoms persist, consult a doctor.

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Protect uninjured eye. Remove contact lenses, if present and easy to do. Continue rinsing.

After swallowing:

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Do NOT induce vomiting. Give nothing to eat or drink.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

(Contd. on page 3)



Date Printed 27.02.2019 Version number 1 Revision Date 21.02.2019

Trade name: 4-methylpentan-2-one

(Contd. of page 2)

• 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

140 futiler relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Water spray, ABC-powder, Carbon dioxide (CO₂), Nitrogen (N₂).
- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon dioxide (CO₂), Carbon monoxide (CO).

- 5.3 Advice for firefighters DO NOT fight fire when fire reaches explosives.
- · **Protective equipment:** Positive pressure self-contained breathing apparatus.
- · Additional information

Do not allow run-off from fire-fighting to enter drains or water courses. Do not inhale explosion and combustion gases. Use caution when applying carbon dioxide in confined spaces. Carbon dioxide can displace oxygen. Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective gloves and glasses.

Special danger of slipping by leaking/spilling product. In case of major fire and large quantities: Remove persons to safety. Wear a self-contained breathing apparatus and chemical protective clothing.

· 6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Do not allow to enter into soil/subsoil.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

Spilled product must never be returned to the original container for recycling. Take up carefully when dry. Take up dust-free and set down dust-free. Clean contaminated objects and areas thoroughly observing environmental regulations.

Clear spills immediately.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Avoid: Inhalation Avoid contact with skin and eyes. Use extractor hood (laboratory). If handled uncovered, arrangements with local exhaust ventilation have to be used. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means. Handle under (Gas): Nitrogen.

· Information about fire - and explosion protection:

The dried resin is combustible, similar to wood. Burning dry resin emits dense, black smoke. As latex, material is not combustible.

Protect against electrostatic charges.

· 7.2 Conditions for safe storage, including any incompatibilities

Storage class: 3

Keep container tightly closed in a cool, well-ventilated place.

(Contd. on page 4)



Date Printed 27.02.2019 Version number 1 Revision Date 21.02.2019

Trade name: 4-methylpentan-2-one

(Contd. of page 3)

· Storage:

· Requirements to be met by storerooms and receptacles:

Store in a cool location.

Storage temperature: 15-25 °C

Information about storage in one common storage facility:

Keep/Store away from combustible materials.

· Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

108-10-1 4-methylpentan-2-one

WEL Short-term value: 416 mg/m³, 100 ppm Long-term value: 208 mg/m³, 50 ppm Sk, BMGV

· Ingredients with biological limit values:

108-10-1 4-methylpentan-2-one

BMGV 20 µmol/L

Medium: urine

Sampling time: post shift

Parameter: 4-methylpentan-2-one

· Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

Technical measures and the application of suitable work processes have priority over personal protection equipment. If handled uncovered, arrangements with local exhaust ventilation have to be used.

- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Wear suitable protective clothing. When handling with chemical substances, protective clothing with CE-labels including the four control digits must be worn. For the protection against direct skin contact, body protective clothing is essential (in addition to the usual working clothes).

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Respiratory protection necessary at: aerosol or mist formation.

Suitable respiratory protection apparatus: Full-/half-/quarter-face masks (DIN EN 136/140)

Recommendation: VWR 111-0206 Suitable material: A2B2E2K2P3 Recommendation: VWR 111-0059

Protection of hands:





Date Printed 27.02.2019 Version number 1 Revision Date 21.02.2019

Trade name: 4-methylpentan-2-one

(Contd. of page 4)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. Recommended glove articles DIN-/EN-Norms: DIN EN 374. In the case of wanting to use the gloves again, clean them before taking off and air them well.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

By short-term hand contact

Suitable material: NBR (Nitrile rubber)
Thickness of the glove material: 0,425 mm

Breakthrough time (maximum wearing time): 37 min Recommended glove articles: VWR 112-0971.

By long-term hand contact

Suitable material: Butyl caoutchouc (butyl rubber)

Thickness of the glove material: 0,50 mm

Breakthrough time (maximum wearing time): 240-480 min

Recommended glove articles: VWR 112-1570.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eve protection:



Tightly sealed goggles

Eye glasses with side protection DIN-/EN-Norms: DIN EN 166

Recommendation: VWR 111-0432

· Body protection:

Wash hands before breaks and after work. Avoid contact with skin and eyes. When using do not eat, drink or smoke. Provide eye shower and label its location conspicuously.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Fluid
Colour: Colourless
Odour: Characteristic
Odour threshold: Not determined.

· **pH-value:** Not determined.

· Change in condition

Melting point/freezing point: $-84~^{\circ}\text{C}$ Initial boiling point and boiling range: 117.4 $^{\circ}\text{C}$

· Flash point: 16 °C

• Flammability (solid, gas): Highly flammable liquid and vapour.

· Ignition temperature: 460 °C

(Contd. on page 6)



Date Printed 27.02.2019 Version number 1 Revision Date 21.02.2019

Trade name: 4-methylpentan-2-one

	(Contd. of page	
Decomposition temperature:	Not determined.	
Auto-ignition temperature:	Not determined.	
Explosive properties:	Product is not explosive. However, formation o explosive air/vapour mixtures are possible.	
Explosion limits:		
Lower:	1.4 Vol %	
Upper:	8 Vol %	
Vapour pressure at 20 °C:	21 hPa	
Density at 20 °C:	0.801 g/cm³	
Relative density	Not determined.	
Vapour density at 20 °C	3.45 (air=1)	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
water at 20 °C:	18 g/l	
Partition coefficient: n-octanol/water:	Not determined.	
Viscosity:		
Dynamic at 20 °C:	0.59 mPas	
Kinematic:	Not determined.	
9.2 Other information	Refraction index 1.396 (589nm, 20°C)	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No data available
- 10.2 Chemical stability No data available
- · Thermal decomposition / conditions to be avoided: No data available
- 10.3 Possibility of hazardous reactions No data available
- · 10.4 Conditions to avoid No data available
- · 10.5 Incompatible materials: No data available
- 10.6 Hazardous decomposition products: No data available

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity

Harmful if inhaled.

· LD/LC50 values relevant for classification:

Oral	LD50	2,080 mg/kg (rat)
		16,000 mg/kg (rab)
Inhalative	LC50/4 h	8.3-16.6 mg/l (rat)

- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation

Causes serious eye irritation.

Causes serious eye irritation.

Respiratory or skin sensitisation

In case of skin contact: not sensitising.

After inhalation: not sensitising.

· Other information (about experimental toxicology):

Carcinogenicity: No indication of human carcinogenicity.

Germ cell mutagenicity: No indications of human germ cell mutagenicity exist.

Reproductive toxicity: No indications of human reproductive toxicity exist.

(Contd. on page 7)



Date Printed 27.02.2019 Version number 1 **Revision Date 21.02.2019**

Trade name: 4-methylpentan-2-one

(Contd. of page 6)

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure
- May cause respiratory irritation.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity No data available.
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential Partition coefficient: n-octanol/water: 1.31
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- General notes:

Water hazard class 1 (German Regulation) (Assessment by list): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage

Dispose according to local legislation. Consult the appropriate local waste disposal expert about waste disposal. Send to a hazardous waste incinerator facility under observation of official regulations.

Recommendation:

Dispose according to local legislation. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

· 14.1 UN-Nur	mber
---------------	------

· ADR, IMDG, IATA UN1263

· 14.2 UN proper shipping name

· ADR **1263 PAINT**

· IMDG, IATA **PAINT**

(Contd. on page 8)



Date Printed 27.02.2019 Version number 1 Revision Date 21.02.2019

Trade name: 4-methylpentan-2-one

(Contd. of page 7)

· 14.3 Transport hazard class(es)

· ADR, IMDG, IATA



· Class 3 Flammable liquids.

· Label 3

· 14.4 Packing group

· ADR, IMDG, IATA

• 14.5 Environmental hazards: Not applicable.

• 14.6 Special precautions for user Warning: Flammable liquids.

Danger code (Kemler): 3
 EMS Number: F-E,S-E
 Stowage Category B

· 14.7 Transport in bulk according to Annex II

of Marpol and the IBC Code Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ) 5L

Excepted quantities (EQ) Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

Transport categoryTunnel restriction codeD/E

· IMDG

· Limited quantities (LQ) 1L

· Excepted quantities (EQ) Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· UN "Model Regulation": UN 1263 PAINT, 3, II

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Water hazard class (WGK): slightly hazardous to water (WGK 1)

EU: Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC (Text with EEA relevance)

EU: Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (Text with EEA relevance)

EU: Commission Regulation (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (Text with EEA relevance)

(Contd. on page 9)



Date Printed 27.02.2019 Version number 1 Revision Date 21.02.2019

Trade name: 4-methylpentan-2-one

(Contd. of page 8)

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I Substance is not listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 40
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge and should assist the user with the safe handling of this material when properly applied. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Sales department
- · Contact:

sales@agarscientific.com Tel: +44 (0) 1279 813 519

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2

Acute Tox. 4: Acute toxicity - Category 4

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

- GE

Distribution in the UK & Ireland



Characterisation, Measurement & Analysis Lambda Photometrics Limited Lambda House Batford Mill Harpenden Herts AL5 5BZ United Kingdom

E: info@lambdaphoto.co.uk W: www.lambdaphoto.co.uk T: +44 (0)1582 764334

F: +44 (0)1582 712084