

9.5 GHz Compact USB Real-Time Spectrum Analyzer

Distribution in the UK & Ireland

SAE-90

Product Brochure V1.1

2023-10-18



- 9 kHz~9.5 GHz real-time spectrum analyzer
- Superheterodyne digital receiver architecture, 14 segments pre-selected filter
- 9 kHz~9.5 GHz typical image suppression>90 dB, typical IF rejection>90 dB
- 100MHz analysis bandwidth with adjustable sampling rate, 1.2 THz/sec spectrum sweep speed
- FPGA based digital signal processing
- Core module supported, light as 185g, size 118×60×15mm, power consumption 10-14W
- Highly compatible API interfaces and SASudio4 GUI
- Compatible with ARM and x86 processors, Linux and Windows operating systems
- Built-in OCXO (option), temperature drift≤0.15 ppm
- Operating temperatures range from - 20 °C/- 40 °C to 65 °C (option)
- USB 3.0/2.0 Type-C interface



SAE-90 Technical Specifications * (typical value)

Indicator test basis Hardware version: R2 API: 0.50.1 FPGA: 0.50.0 MCU: 0.50.2 SAS4: 4.50.40

Frequency				
Frequency Range	9 kHz~9.5 GHz			
Initial Frequency Accuracy	<1 ppm, Supporting program manual correction			
Reference Clock	Internal or external, program-controlled switching, Internal TCXO aging<1 ppm/year, temperature drift<1 ppm; Internal OCXO (option), temperature drift ≤0.15 ppm			
Spectrum Purity				
SSB Phase Noise	dBc/Hz			
Carrier Frequency	1 GHz	3 GHz	6 GHz	9 GHz
1 kHz	-95.2	-96.6	-93.9	-91.5
10 kHz	-101.6	-102.6	-101.6	-98.5
100 kHz	-100.6	-103.9	-103.2	-99.7
1 MHz	-120.9	-121.8	-120.3	-116.2
10 MHz	-134.2	-133.5	-134.2	-131.4
Residual Response Spurious rejection off dBm RBW =1 kHz Positive Peak Detector	Frequency Range	R.L.=0 dBm	R.L.=-20 dBm	R.L.=-50 dBm
	9 kHz~1.0 GHz	< -83	< -110	< -120
	1.0 GHz~3.0 GHz	< -83	< -92	< -120
	3.0 GHz~9.5 GHz	< -90	< -100	< -130
Image Frequency Suppression	100 kHz~3.0 GHz	>90 dBc (spurious rejection on), >90 dBc (spurious rejection off)		
	3.0 GHz~9.5 GHz	>60 dBc (spurious rejection off), >90 dBc (spurious rejection on)		
IF rejection (R.L.=0 dB)	>90 dBc (spurious rejection on), >80 dBc (spurious rejection off)			
Local Oscillator Related Spurious	<-65 dBc (Offset Center Frequency +/- (N/M)*125MHz, N = 1,2,3,4,5...)			
Input Related Spurious	<-75 dBc (spurious rejection on), <-50 dBc (spurious rejection off)			
Linearity				
IIP3 (dBm) 2 MHz interval -6 dBFs/Tone	1 GHz	3 GHz	9 GHz	
R.L.= 20 dBm	48.1	45.1	40.5	
R.L.= 0 dBm	26.7	23.5	21.2	
R.L.= -20 dBm	5.1	2.6	-0.9	
R.L.= -50 dBm	-21.2	-22.6	-22.9	
Signal Processing				
Analysis Bandwidth	Maximum 100 MHz, Decimate Factor:1			
IQ Data	122.88 MSPS, supporting 120 MSPS-125 MSPS program adjustable, 1 Hz step Decimate factor: 1,2,4,8,16,32,64,128,256,512,1024,2048,4096 supported (FPGA)			
Storage Depth	The built-in memory depth is 128 Mbytes			
	Supports continuous and uninterrupted storage when the data generation rate is less than the bus bandwidth, and the storage depth is only limited by the hard disk capacity			
External Trigger Response	Maximum response frequency 500 times/sec			
Analog IF Output	Supporting 307.2 MHz +/-50 MHz			
Amplitude				
Maximum safe input power	23 dBm	50 MHz~9.5 GHz and the preamplifier off (R.L. ≥ 0 dBm)		

(CW)	10 dBm	100 kHz~50 MHz or preamplifier on (R.L. <0 dBm)		
Maximum DC Voltage	±12 VDC			
Display Range	DANL~23 dBm			
Amplitude Accuracy	±2.0 dB			
IF in-band spectrum ripple	±2.0 dB (100 MHz analog IF bandwidth)			
Reference level (R.L.)	-50 dBm~23 dBm			
RF Preamplifiers	Converting bands (frequency ≥ 50MHz) are equipped with preamplifier that can be set as automatically turn on or forcibly turn off			
Display Average Noise Level (DANL) dBm/Hz RBW=10kHz RMS detector	Frequency Range	R.L.= 0 dBm (IFGainGrade = 2)	R.L.= -20 dBm (IFGainGrade = 2)	R.L.= -50 dBm (IFGainGrade = 2)
	9 kHz	-90.1	-105.7	-115.6
	1 MHz~100 MHz	-134.2	-146.3	-150.9
	100 MHz~3.0 GHz	-131.0	-145.7	-165.1
	3.0 GHz~6.0 GHz	-136.2	-150.2	-164.6
6.0 GHz~9.5 GHz	-135.4	-148.9	-157.4	
Standard Spectrum Analysis				
Detector	Positive peak, Negative peak, Sampling, Average, RMS, Max Power			
RBW	0.1 Hz~10 MHz			
VBW	0.1 Hz~10 MHz			
Trace Function	Sample, Positive Peak, Negative Peak, Local average, Maximum hold, Minimum hold, Average			
Data Chart	SAStudio4 software provides regular spectrum, waterfall chart, and historical trace			
Measurements	Phase noise, Channel power, Occupied bandwidth, X dB bandwidth, Adjacent channel suppression, IM3			
Sweep speed - Standard Spectrum Analysis	1.2 THz/s	FPGA	RBW≥1 MHz, B-Nuttal window, spurious rejection: Bypass	
	564.4 GHz/s	FPGA	RBW=250 kHz, B-Nuttal window, spurious rejection: Standard	
	65.2 GHz/s	FPGA	RBW=30 kHz, B-Nuttal window, spurious rejection: Bypass	
	2.7 GHz/s	CPU	RBW=1 kHz, B-Nuttal window, spurious rejection: Bypass	
Detection Analysis/Zero Span				
Highest Time Resolution	8 ns			
Maximum Analysis Bandwidth	100 MHz			
Trace Detection	Positive peak, Negative peak, Sampling, Average, RMS, Max Power			
Real Time Spectrum Analysis				
FFT Analysis	Variable point FFT engine implemented by FPGA. frame rate compression and trace detection are supported. There is strictly no gap and overlap between FFT frames.			
	FFT refresh rate= $10^9 \text{ ns}/(N * D * 8 \text{ ns})$; POI = $2 * N * D * 8 \text{ ns}$ N is the number of FFT points (2048, 1024, 512, 256, 128, 64, 32), and D is the decimate factor (1, 2, 4, 8...)			
	Typical Settings	FFT Refresh Rate		POI
	N = 2048, D = 1	61,035 times /second		32.768 us
	N = 32, D = 1	3,906,250 times /second		0.512 us
Real-time Analysis Bandwidth	100 MHz			
Window Function	B-Nuttall, FlatTop			

RBW	14.73 MHz-3.59 kHz (FlatTop window); 7.81 MHz~1.90 kHz (B-Nuttall) ;13 grades for each window type	
Amplitude Resolution	0.75 dB	
General		
Input And Output	Power Supply	Type-C (1), dedicated power supply port, please provide 5V 2A peak power supply capacity Allowable voltage range: 4.75~5.25 V, ripple less than 200 mVpp
	Data	Type-C (2), USB3.0 (USB2.0 Available but bandwidth limited)
	RF input	2.92 mm (F), Input impedance 50 Ω
	External reference clock input	MMCX (F) (1), amplitude ≥ 1.5 Vpp, input impedance 330 Ω
	External reference clock output	Integrated in MUXIO, 3.3 V CMOS, programmable on/off
	External trigger input	Integrated in MUXIO, 3.3 V CMOS, input: high impedance
	External trigger output	Integrated in MUXIO, 3.3 V CMOS
	Analog IF Output	MMCX (F) (2), maximum output power – 25 dBm, output impedance 50Ω
Power Consumption	Peak: 14 W, typical: 10 W~14 W	
Operating Temperature (ambient temperature /core temperature)	0~50 °C/0~70 °C (Standard temperature class)	
	-20~65 °C/-20~85 °C (Extended Temperature Class Option) (plastic enclosure and fan not included)	
	-40~65 °C/-40~85 °C (Wide Temperature Class Option) (plastic enclosure and fan not included)	
Storage Temperature (ambient temperature)	-20~70 °C (Standard temperature class)	
	-40~85 °C (Extended temperature class and wide temperature options) (plastic enclosure and fan not included)	
Size (D * W * H) and weight	118 x60 x15 mm, 188 g (excluding protective shell and structural fittings, including joint length) 132 x70 x29 mm, 375 g (including protective shell and structural fittings, including joint length)	
Packaging and Accessories	Flash disk * 1, USB 3.0 cable * 2, Power adapter * 1	

*The typical values of the indicators are applicable for the following conditions: (1) Start up and warm up for 10 minutes; (2) Ambient temperature 25 °C (core temperature 50 °C); (3) Spurious suppression off; (4) 100MHz analog IF and IFGainGrade=2; (5) The user shall provide the necessary heat dissipation conditions to ensure that the ambient temperature and the core temperature of the equipment are within the rated range at the same time.

Code Name	Option	Explanation
01	Built-in OCXO reference clock (hardware opt.)	Providing a reference clock with better stability than the standard configuration, with a temperature drift of <0.15 ppm, increasing the overall power consumption by 0.8 W.
10	IO extension board (accessory)	Converting the MUXIO interface into multiple MMCX and board to wire connector to facilitate the connection of trigger input, output, and other signals.
11	External GNSS (accessory)	Standard GNSS module connected to MUXIO.
12	External high precision GNSS (accessory)	High precision GNSS module connected to MUXIO.
13	External GNSS disciplined OCXO reference clock (accessory)	Providing GNSS disciplined reference clock and 1PPS, increasing the overall power consumption by 1.1W.
20	Extended temperature class (hardware opt.)	- 20~65 °C/- 20~85 °C(Extended temperature class opt.)
21	Wide temperature class (hardware opt.)	- 40~65 °C/- 40~85 °C(Wide temperature class opt.)

Distribution in the UK & Ireland



Lambda Photometrics Limited
 Lambda House Batford Mill
 Harpenden Herts AL5 5BZ
 United Kingdom

**Characterisation,
 Measurement &
 Analysis**

E: info@lambdaphoto.co.uk
 W: www.lambdaphoto.co.uk
 T: +44 (0)1582 764334
 F: +44 (0)1582 712084