

# **IXDICE ULTRA 1342**

Diode laser pumped Q-switched solid-state laser Wavelength 1342 nm Average power 18 W



### **General description**

The IXDICE Ultra 1342 is a high repetition rate all-solid-state diode pumped Q-switched laser with the unique fundamental wavelength of 1342 nm. It is the amplified high power version of the IXDICE 1342 laser. With an average output power of 18 W it is the most powerful system on the market at this special wavelength.

The laser is optimized for high pulse repetition rates in the range 30 to 200 kHz to allow high throughput in material processing applications. Due to its high pulse-to-pulse stability and the sealed housing, the IXCDICE Ultra 1342 is well suited for continuous 24/7 industrial use.

With a wavelength of 1342 nm, the IXDICE Ultra 1342 is a perfect choice as a laser tool for silicon processing like stealth dicing or trimming of integrated circuits.

### **Applications**

Stealth dicing
Wavelength sensitive processes
Silicon processing
Micro-machining

Product specifications		
Model	IXDICE 1342	
Wavelength	1342 nm	
Average power	18 W	
Pulse duration	typ. 40-50 ns	
Energy per pulse	500 μJ @ 30 kHz	
Repetitipon rate	30-200 kHz	
M²	< 1.3	

Data at 100 kHz pulse repetition rate, except otherwise stated. Specifications are subject to change without notice due to product improvement.

#### **Features**

High repetition rate, up to 200 kHz
Graphical user interface
LabVIEW libraries
CDRH compliance

Distribution in the UK & Ireland




Lambda Photometrics Limited Lambda House Batford Mill Harpenden Herts AL5 5BZ United Kingdom


E: info@lambdaphoto.co.uk W: www.lambdaphoto.co.uk T: +44 (0)1582 764334 F: +44 (0)1582 712084




# **IXDICE ULTRA 1342**

### **Typical performance**







### **Typical beam profile**



## **Dimensions laser head**







	26	161	ļ .
<b>+</b>	<del>•</del>	•	75

# System dimensions (L x W x H), weight

Laser head	600 x 428 x 118 mm <sup>3</sup>	39.0 kg
<b>Power supply</b> 528 x 483 x 134 mm <sup>3</sup> 18.0 kg		18.0 kg
<b>Chiller</b> 611 x 482 x 134 mm		16.6 kg

<b>Electrical characteristics</b>			
Operating voltage	85-264 VAC		
Frequency	47-63 Hz		
Power consumption	600 W typ		

Complies with 21 CFR 1040.10 and 1040.11 except for deviations pursuant to Laser Notice No. 50, dated June 24, 2007 Class 4 laser (IEC 60825-1)



Distribution in the UK & Ireland

