

SYSTEM	
ZYGO P/N	6306-0360-04 system with full enclosure 6306-0360-05 system with 1/2 height enclosure
Measurement Technique	3D coherence scanning interferometry, SureScan™ technology
Scanner	Precision Piezo drive with Closed loop capacitance gauge control and crash protection
Objectives	1.0X – 100X magnification; Standard and long working distance; See the Nexview & NewView 9000 Series Objective Chart for more details
Objective Mounting Options	<ul style="list-style-type: none"> • Single objective dovetail • Manual Encoded 4-position turret • Motorized 4-position turret
Optical Zoom	Motorized 3-position encoded zoom • 0.5X, 1.0X, 2.0X included • 0.75X, 1.5X optional
Field of View	Objective and zoom selectable from 0.04 x 0.04 mm to 17.49 x 17.49 mm; Integrated field stitching for larger areas
Illuminator	Proprietary solid-state white light source with software-selectable field stop, aperture stop and spectral filters
Measurement Array	Selectable 1600 x 1200, 1000 x 1000, 1000 x 600, 1000 x 200
Part Viewing	Selectable Monochrome imaging with available fringe-free viewing mode
Focus	Motorized manual or auto focus with Part Finder and Smart Setup Technology
Z-Drive (Focus) Stage	150 mm range with 0.1 µm resolution
Part Stage	Encoded linear motor drive with 650 x 650 mm XY travel range
Stage Configuration	Split axis gantry style; X-stage translates Head; Y-stage translates the sample
Sample Holder	Custom vacuum sample holders up to 650 x 650 mm available
System Controller	i7 class PC with 1080P display
Software	ZYGO Mx software running under Microsoft Windows 10 (64-bit)

PHYSICAL	
Dimensions (HWD)	System with enclosure: 166 x 140 x 164 cm
Weight	System: 1830 kg System with enclosure: 1955 kg

UTILITY REQUIREMENTS	
Input Voltage	100 to 240 VAC, 50/60 Hz
Compressed Air for isolation	4.1 to 5.5 bar (60 to 80 psi); dry and filtered; 1/4 in. input
Vacuum	Optional from a customer supplied source, based on part stage requirements

PERFORMANCE	
Vertical Scan Range	150 µm with precision Piezo drive; 20 mm with extended scan
Surface Topography Repeatability ⁽¹⁾	0.12 nm
Repeatability of RMS ⁽²⁾	0.01 nm
Optical Lateral Resolution ⁽³⁾	0.34 µm (100X objective)
Spatial Sampling	0.04 µm (100X objective 2X zoom)
Maximum Data Scan Speed ⁽⁴⁾	53 µm/sec @ 1600 x 1200 69 µm/sec @ 1000 x 1000 107 µm/sec @ 1000 x 600 171 µm/sec @ 1000 x 200
Step Height Repeatability ⁽⁵⁾	0.1%
Step Height Accuracy ⁽⁶⁾	0.3%

TEST PART CHARACTERISTICS	
Material	Opaque, transparent, coated, uncoated, specular, rough
Maximum Sample Height	260 mm under X axis Crossbeam 329 mm under typ. objective focus
Maximum Surface Slope	55° – smooth part @ 100X 85° – scattering surface
Sample Reflectivity	0.05% - 100%

ENVIRONMENTAL REQUIREMENTS	
Temperature	15 to 30°C with rate of change <1.0°C per 15 min
Humidity	5 to 95% relative, noncondensing
Vibration Isolation	Included and required for vibration in the range of 1 Hz to 120 Hz
Vibration Criterion	VC-C or better
Acoustic Criterion	NC30 or better

FOOTNOTES

- Performance specifications under laboratory conditions using standard specimens, according to ISO 25178-601, 25178-604 and 5436-1.*
- (1) Surface Topography Repeatability for CSI mode, 1-sec acquisition, full FOV with 3x3 median filter, in a laboratory environment.
 - (2) Repeatability of the RMS surface roughness parameter Sq, under the same conditions as for (1). Note that the repeatability of the Sq is sometimes referred to informally as "vertical resolution."
 - (3) Lateral Resolution=Sparrow criterion, objective dependent.
 - (4) Data scan speed depends on the measurement array and data acquisition mode.
 - (5) 1-σ Step height repeatability verified using 1.8 µm and 24 µm ZYGO certified step height standards.
 - (6) Instrument contribution to uncertainty for step height measurements using the piezo drive.

Distribution in the UK & Ireland



Lambda Photometrics Limited
 Lambda House Batford Mill
 Harpenden Herts AL5 5BZ
 United Kingdom

**Characterisation,
 Measurement &
 Analysis**

E: info@lambdaphoto.co.uk
W: www.lambdaphoto.co.uk
T: +44 (0)1582 764334
F: +44 (0)1582 712084